

# THINK CREATE PRINT



## PMCS 4131DW

25PPM.512MB RAM.1 GHZ DUAL CORE,DUPLEX.WIRELESS.

FOLLOW US



AVAILABLE ON



Efficient • Transparent • Inclusive

Toll Free No.

**18003099639**

[info@printmark.net.in](mailto:info@printmark.net.in)

[www.printmark.net.in](http://www.printmark.net.in)



Contact US

#startupindia

# PRINTMARK COLOUR LASER PRINTER PMCS 4131dw

Light, compact, and fast, the PMCS4131DW PRINTER supports output up to 25 pages per minute,  
Connect via USB or WIRELESS or Ethernet

	Specification
Print Technology	Laser
Type of Machine	Single Function
Type of Printing	Colour
Cartridge Technology	Composite
Minimum Speed Per Minute as per ISO/IEC 24734 in A4 Size	25 PPM Black & Color both
Time to First Page Out	Black: 10.9 Sec Color: 11 Sec
Print Speed Duplex	26 IPM
Duplexing Feature Availability	Yes
Processor	1 GHz, Dual Core
Memory (RAM)	Standard: 512 MB / Maximum: 512 MB
Display	2.8 inch (7.2 cm) LCD touch panel
Duty Cycle (No of Prints/month)	75000 pages per month
Paper Size (Original/Image)	A4/A4
Number of Main Paper Tray	1
Each Main Paper Tray Capacity	250
Bypass Tray Capacity	1
Output Tray Capacity	100 sheets
Wireless	Yes
Standard Ports	802.11ac Wireless, USB 2.0 Hi-Speed Certified (Type B), Gigabit Ethernet BaseTX (RJ-45)
Network Protocols	TCP/IP IPv6, IPSEC w/ IPv4, IPSEC w/ IPv6, TCP/IP IPv4, ICMP, TCP, IGMP, UDP
Resolution	4800 CQ (2400 x 600 dpi), 2400 CQ (2400 x 600 dpi), , 600 x 600 dpi (default), 300 x 300 dpi
Media Size supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Aficio, A6
Media Type	Paper Labels, Card Stock, Plain Paper, Envelopes
Yield of the cartridge supplied with Machine as per ISO/IEC: 19752/2004(E)	Black 750 & CMY each 500 pages
After market Cartridge Capacity	Black 1500 & CMY each 1500 pages
Imaging Unit Capacity	Composite Technology Toner with Imaging Unit
Print Languages	PCL 5c Emulation, PCL 5e Emulation, PCLm, PCL 6 Emulation, PostScript 3 Emulation, PDF 1.7 emulation, Direct Image
OS Support *	Windows 7 and above, SUSE Linux 12 and above, Ubuntu 16.04 and above, Red Hat Enterprise Linux WS 6.10 and above
Certifications	BIS, ROHS, CE, BEE, NABL Approved
Noise Level	Operating: 53dBA (Print)
Size/Weight	H x W x D: 243.7 x 411.2 x 394.1 mm / 16.1 kg
Warranty	1 Year Onsite Support

All information in this brochure is subject to change without notice. Printmark is not liable for any errors or omissions.

1- Average standard page yield value declared in accordance with ISO/IEC 19752. 2- "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Printmark's product offerings based on the average number of pages customers plan to print on the device each month. Printmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals, paper loading intervals, speed, and typical customer usage. 3- "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Printmark printers and MFPs. 4- Printers are sold subject to certain license/agreement conditions. 5- Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. 6- Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively.

\*For Detailed OS Support Please visit our website [www.printmark.net.in](http://www.printmark.net.in)

© 2024 Printmark. All rights reserved. Printmark, the Printmark logo are trademarks of Printmark Technologies Pvt Ltd, registered in India.

